



Seal-Bore Production Packer Specifications

CASING SIZE				MAXIMUM PACKER O.D.		MODEL TYPE	SEAL-BORE I.D. THRU PACKER		MIN. BORE THRU SEAL NIPPLE		STANDARD THREAD (PIN DOWN)	
O.D.		WEIGHT RANGE					In.	Mm.	In.	Mm.		
In.	Mm.	Lb./Ft.	Kg./M.	In.	Mm.					In.		
4½	114.3	9.5-12.6	14.1-18.7	3¾	95.3	SS	1.968	50.0	1.000	25.4	2⅞ EUE	
		9.5-13.5	14.1-20.1	3 ²⁵ / ₃₂	95.0	SS-BB	2.688	68.3	1.910	48.5		
		9.5-12.6	14.1-18.7	3¾	95.3	SS-R	1.968	50.0	1.000	25.4		
		12.6-15.1	18.7-22.5	3⅝	92.1							
		9.5-11.6	14.1-17.3	3 ¹⁹ / ₁₆	96.8	JE-PR	1.968	50.0	1.000	25.4		
		11.6-13.5	17.3-20.1	3 ²⁵ / ₃₂	95.0							
5	127.0	15.0-18.0	22.3-26.8	4½ ₂	103.9	SS	2.500	63.5	1.875	47.6	3½ NU	
						SS-BB	2.688	68.3	1.910	48.5		
		11.5-13.0	17.1-19.3	4½ ₂	108.7	SS-R	2.500	63.5	1.875	47.6		
		15.0-18.0	22.3-26.8	4¼ ₁₆	103.2							
		11.5-15.5	17.1-23.1	4¼	107.9	JE-PR	2.688	68.3	1.910	48.5		
		15.0-18.0	22.3-26.8	4⅞	104.8							
5½	139.7	14.0-20.0	20.8-29.8	4 ¹⁹ / ₃₂	116.7	SS	2.688	68.3	1.910	48.5	4 NU	
		20.0-23.0	29.8-34.2	4 ¹⁹ / ₃₂	113.5							
		14.0-20.0	20.8-29.8	4 ¹⁹ / ₃₂	116.7	SS-BB	3.000	76.2	2.344	59.5		
		20.0-23.0	29.8-34.2	4 ¹⁹ / ₃₂	113.5							
		14.0-20.0	20.8-29.8	4 ¹⁹ / ₃₂	116.7	SS-R	2.688	68.3	1.910	48.5		
		20.0-23.0	29.8-34.2	4½	114.3							
		13.0-17.0	19.3-25.3	4 ²³ / ₃₂	119.9	JE-PR	3.000	76.2	2.344	59.5		
		20.0-23.0	29.8-34.2	4½	114.3							
7	177.8	26.0-32.0	38.7-47.6	5 ²⁹ / ₃₂	150.1	SS	3.250	82.6	2.437	61.9	4½ 8RFL	
		35.0-38.0	52.1-56.5	5¾	146.1	SS-BB	4.000	101.6	3.000	76.2		
		26.0-32.0	38.7-47.6	5 ²⁹ / ₃₂	150.1							
		26.0-32.0	38.7-47.6	5¾	146.1	SS-R	3.250	82.6	2.437	61.9		
		35.0-38.0	52.1-56.5	5⅝	142.9							
		17.0-20.0	25.3-29.8	6¼	158.8	JE-PR	3.250	82.6	2.437	61.9		
		23.0-26.0	34.2-38.7	6¼ ₁₆	154.0							
		29.0-32.0	43.2-47.6	5 ²⁹ / ₃₂	150.1							
		32.0-35.0	47.6-52.1	5 ¹⁹ / ₁₆	147.6							
		17.0-20.0	25.3-29.8	6¼	158.8		4.000	101.6	3.000	76.2		
		23.0-26.0	34.2-38.7	6¼ ₁₆	154.0							
		29.0-32.0	43.2-47.6	5 ²⁹ / ₃₂	150.1							
		32.0-35.0	47.6-52.1	5 ¹⁹ / ₁₆	147.6							
		7⅞	193.7	20.0-26.4	29.8-39.3	6 ²⁹ / ₃₂	172.2	SS	3.250	82.6		2.437
26.4-33.7	39.3-50.2			6 ³⁷ / ₆₄	167.1	SS-BB	4.000	101.6	3.000	76.2		
33.7-39.0	50.2-58.1			6 ⁷ / ₁₆	163.5							
26.4-33.7	39.3-50.2			6 ³⁷ / ₆₄	167.1	SS-R	3.250	82.6	2.437	61.9		
33.7-39.0	50.2-58.1			6 ⁷ / ₁₆	163.5							
20.0-26.4	29.8-39.3			6 ²⁹ / ₃₂	172.2	JE-PR	3.250	82.6	2.437	61.9		
29.7-33.7	44.2-50.2			6 ³⁷ / ₆₄	167.1							
33.7-39.0	50.2-58.1			6 ⁷ / ₁₆	163.5							
26.4-29.7	39.3-44.2			6 ¹¹ / ₁₆	169.9		4.000	101.6	3.000	76.2		
29.7-33.7	44.2-50.2			6 ³⁷ / ₆₄	167.1							
33.7-39.0	50.2-58.1			6 ⁷ / ₁₆	163.5							
26.4-29.7	39.3-44.2			6 ¹¹ / ₁₆	169.9							
29.7-33.7	44.2-50.2			6 ³⁷ / ₆₄	167.1							
33.7-39.0	50.2-58.1			6 ⁷ / ₁₆	163.5							
9⅝	244.5	36.0-43.5	53.6-64.7	8 ¹⁵ / ₃₂	215.1	SS	4.750	120.7	3.500	88.9	5½ 8RF	
		43.5-53.5	64.7-79.6	8¼	209.6	SS-BB	6.000	152.4	4.813	122.2		
		40.0-47.0	59.5-69.9	8⅝	212.7	SS-R	4.750	120.7	3.000	76.2		
		36.0-43.5	53.6-64.7	8 ¹⁵ / ₃₂	215.1	SS-BB	6.000	152.4	4.813	122.2		
		40.0-47.0	59.5-69.9	8⅝	212.7							
		43.5-53.5	64.7-79.6	8½	215.9	JE-PR	4.750	120.7	3.500	88.9		
		40.0-47.0	59.5-69.9	8⅝	212.7							
		43.5-53.5	64.7-79.6	8¼	209.6							
		36.0-43.5	53.6-64.7	8½	215.9		6.000	152.4	4.813	122.2		
		47.0-53.5	69.9-79.6	8¼	209.6							
		36.0-43.5	53.6-64.7	8½	215.9							
		47.0-53.5	69.9-79.6	8¼	209.6							