



WNT  
Hookwall  
Packer

## WNT Hookwall Packer

**Product:** WNT Packer  
**Type:** Retrievable/Hookwall  
**Set:** Mechanical  
**Retrieve:** Right-Hand Rotation

The TIW WNT Packer is designed for many applications: production, injection, zone isolation, waterflood, gas lift and pumping.

### Advantages

- Reliable right-hand set, mechanical lock, right-hand release design.
- Cage-protected, bi-directional slips require no hydraulic hold-downs.
- Slips hold pressure from above or below whether in tension, in neutral or with setdown weight applied to packer.
- Versatile design allows packer to change from: 1) weight-set through neutral to tension or 2) from tension through neutral to weight-set, without moving or leaking.
- Large fluid bypass area through the packer allows fast running, proper equalization.

### WNT Hookwall Packer Specifications

CASING SIZE				NOMINAL TUBING SIZE O.D.		PACKER BODY				STANDARD THREAD CONNECTIONS (BOX UP, BOX DOWN)
O.D.		WEIGHT				MAX. O.D.		I.D.		
In.	Mm.	Lb./Ft.	Kg./M.	In.	Mm.	In.	Mm.	In.	Mm.	In.
4½	114.3	9.5	14.1	2¾	60.3	3.750	95.3	1.937	49.2	2¾ EUE 8RD
		13.5	20.1			4.125	104.8	1.937	49.2	
5	127.0	11.5	17.1	2¾	60.3	4.062	103.2	1.937	49.2	
		15.0	22.3			4.500	114.3	2.000	50.8	
5½	139.7	14.0	20.8	2¾	60.3	4.625	117.5	2.000	50.8	
		20.0	29.8			4.500	114.3	2.000	50.8	
5½	139.7	14.0	20.8	2¾	73.0	4.625	117.5	2.375	60.3	2¾ EUE 8RD
		20.0	29.8			4.500	114.3	2.375	60.3	
7	177.8	20.0	29.8	2¾	73.0	5.906	150.0	2.375	60.3	
		26.0	38.7			5.750	146.0	2.375	60.3	
		32.0	47.6			5.625	142.9			
		35.0-38.0	52.1-56.6							
7½	193.7	20.0	29.8	2¾	73.0	6.781	172.2	2.375	60.3	
		26.4	39.3			6.578	167.1	2.375	60.3	
		33.7	50.2			6.437	163.5	2.375	60.3	
		39.0	58.1							
9½	244.5	32.0	47.6	4	101.6	8.375	212.7	3.500	88.9	4 EUE 8RD
		47.0	69.9			8.250	209.6	3.500	88.9	
		43.5	64.7							
		53.5	79.6							